



**Specifications Ledvance LED  
Downlight Performance DN195 21W  
2400lm 65D - 830 Warm White |  
220mm - IP54**

[View Product](#)

## General Information

|                          |                                    |
|--------------------------|------------------------------------|
| SKU                      | 238964                             |
| EAN                      | 4058075459250                      |
| Manufacturer Code        | 4058075459250                      |
| Brand                    | Ledvance                           |
| Manufacturer Name        | DL UGR19 DN195 PFM 21W/830 WT IP54 |
| Any Lamp all-in warranty | 5 Years                            |
| Average Lifetime (h)     | 70000                              |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Wattage                     | 21W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                         |                                |
|-------------------------|--------------------------------|
| Driver Included         | Yes                            |
| Beam Angle (degree)     | 65                             |
| Luminous Flux (Lumen)   | 2400lm                         |
| Lumen per watt          | 115                            |
| Power factor            | >0.90                          |
| Installation Depth (mm) | 120                            |
| Unified Glare Rating    | < 19 - for offices and schools |
| Optical Cover           | PC (Polycarbonate)             |
| Product Type Category   | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 195               |
| IP-Rating              | IP54              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +45        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Fixture Connection     | Screw terminal    |
| Series                 | DN195             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 82  |
| Diameter (mm) | 220 |

## Sensor Information

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

